

This page describes the predefined [Wiki Styles](#) and how a [Wiki Administrator](#) can define additional [Wiki Styles](#) as a local customization for all pages (in local/config.php) or specific groups (in local/\$Group.php).

All predefined [Wiki Styles](#) are setup in the global array `$WikiStyle`. To define your own [Wiki Styles](#), add the setting of the correspondent WikiStyle within the array.

Predefined Wiki Styles

The following array-values are set by scripts/wikistyles.php using the [SDV\(\)-function](#) (so you can overwrite them by setting them prior in config.php or farmconfig.php):

markup:	definition:
text colors: (equiv.to %define=xxxx color=xxxx%)	
%black%	\$WikiStyle['black']['color'] = 'black';
%white%	\$WikiStyle['white']['color'] = 'white';
%red%	\$WikiStyle['red']['color'] = 'red';
%yellow%	\$WikiStyle['yellow']['color'] = 'yellow';
%blue%	\$WikiStyle['blue']['color'] = 'blue';
%gray%	\$WikiStyle['gray']['color'] = 'gray';
%silver%	\$WikiStyle['silver']['color'] = 'silver';
%maroon%	\$WikiStyle['maroon']['color'] = 'maroon';
%green%	\$WikiStyle['green']['color'] = 'green';
%navy%	\$WikiStyle['navy']['color'] = 'navy';
%purple%	\$WikiStyle['purple']['color'] = 'purple';
list-styles:	
%decimal%	\$WikiStyle['decimal']['apply'] = 'list'; \$WikiStyle['decimal']['list-style'] = 'decimal';
%roman%	\$WikiStyle['roman']['apply'] = 'list'; \$WikiStyle['roman']['list-style'] = 'lower-roman';
%ROMAN%	\$WikiStyle['ROMAN']['apply'] = 'list'; \$WikiStyle['ROMAN']['list-style'] = 'upper-roman';
%alpha%	\$WikiStyle['alpha']['apply'] = 'list'; \$WikiStyle['alpha']['list-style'] = 'lower-alpha';
%ALPHA%	\$WikiStyle['ALPHA']['apply'] = 'list'; \$WikiStyle['ALPHA']['list-style'] = 'upper-alpha';
special:	
open links in a new browser-window:	
%newwin%	\$WikiStyle['newwin']['target'] = '_blank';
Turns markup into a comment via display:none CSS	
%comment%	\$WikiStyle['comment']['display'] = 'none';

Author-Defined Wiki Styles

1. The first index of the array defines the style name (e.g. mynewstyle, projectentry etc)
2. the second index defines the attribute name (e.g. color, background-color, etc.)
3. the value set defines the attribute value (e.g. red, bold, #00ffcc, etc.)

Sample: If you want to define a (site-wide) style the same as the page style

```
%define=projectentry color:red%
```

```
use
```

```
$WikiStyle['projectentry']['color'] = 'red';
```

The `$WikiStyle['projectentry']['apply']` variable may be defined if the wikistyle concerns a particular tag. It may be 'item' (for `li|dt`), 'list' (for `ul|ol|dl`), 'div', 'pre', 'img', 'p' or the combining 'block' (for `p|div|ul|ol|dl|li|dt|pre|h[1-6]`). Example:

```
$WikiStyle['top']['apply'] = 'item'; $WikiStyle['top']['class'] = 'top';
```

then a markup

```
* %top% An important list-item
```

will output

```
<li class="top">An important list-item</li>
```

Printer-Friendly Styles

If your custom-styles (in `local/config.php`) are getting very colorful it might be useful to disable them in print-view. This can be done easily by putting them into a condition.

```
if($action!="print") {
    // your custom-styles
}
```

Notes

To be done:

Questions:

I tried this but background didn't work, thou border and float worked? /Vincent 2008-04-08

```
$WikiStyle['vMenu']['background']='#ffffcc' ;
$WikiStyle['vMenu']['float']='left' ;
$WikiStyle['vMenu']['border']='1px dotted red' ;
```

Try using `$WikiStyle['vMenu']['background-color']='#ffffcc'`; -- unlike background, background-color is defined in the `$WikiStyleCSS` array, which is checked for valid properties.

Copyright: Petko - 14/02/2009